

Lubricated Air Cooled Reciprocating Compressors 5 - 20 HP




Compressor Specifications

- Splash Lubricated
- Two Stage Design
- 100% Cast Iron Compressor Pump
- Alloy Steel Reed Valve
- Oil Level Site Glass
- Deep Finned Intercooler
- Industrial Grade Intake Filter & Silencer
- All Pumps Factory Tested Prior to Shipment

Standard Equipment

- Automatic Start & Stop Operation
- Horizontal Air Receiver
- 415V/3 Phase/50 Hz Electric Motor
- DOL Starter
- Belt Guard
- V-Belt Drive Arrangement
- Safety Valve
- Discharge & Drain Valve



Technical Specifications

Lubricated Air Cooled Reciprocating Compressors 5 - 20 HP

Bare Model	Moter (hp)	Receiver Size (ltrs)	Compressor (rpm)	Bore and Stroke (inch)	PD (cfm)	Working Pressure (acfm)		
						125 psig	150 psig	175 psig
RV15	5	225	630	4-5/8" & 2-1/2" x 3"	18.4	15.6	15.5	15.3
	7.5	225/300	910		26.5	23.7	23.4	23.2
RV30	10	300/500	640	4-5/8" & 4-5/8" & 2-1/2" & 2-1/2" x 3"	37.3	30.2	30.1	30
	12.5	300/500	740		43.2	35.3	35.1	35
	15	300/500	910		53.1	44.4	43.9	43.5
	20	300/500	1010		58.9	49.5	49.3	49

^{*} acfm may vary within ±5% in accordance to IS 5456

Product image is for illustration purpose only, actual Product may vary. Gardner Denver policy is one of continuous improvement and we therefore reserve the right to alter specifications and prices without prior notice. All products are sold subject to the Company's conditions of sale.







Gardner Denver Engineered Products India Private Limited

Plot No. 878, Opp. Gallops Industrial Park, Sarkhej-Bavla Road, Taluka Bavla, Village Rajoda, Ahmedabad - 382220,

Gujarat, India.

Ph.: +91 79 40089312 / +91 2714 619300 Fx.: +91 79 40089313 / +91 2714 619329 Email: info.ahm@gardnerdenver.com